

FLEXIBLE BOOTS MEETING  
ASTM C923 CLAMP-ON TYPE  
(CAST-IN BOOT SHOWN;  
PRESSED-IN BOOT ALSO  
PERMITTED)

FLEXIBLE BOOTS  
MEETING ASTM C923  
"A-LOCK" TYPE

CLAMP SECURELY IN  
ACCORDANCE WITH BOOT MFR'S  
INSTRUCTIONS. USE A MINIMUM  
OF 2 STAINLESS STEEL CLAMPS.

INVERT CHANNEL  
CONCRETE

INSTALL PIPE IN  
ACCORDANCE WITH BOOT  
MFR'S INST.

OR

WHEN PLACING FIELD-POURED  
INVERT CHANNELS, PACK  
ANNULAR SPACES WITH  
EXTRUDIBLE PREFORMED  
PLASTIC GASKET MATERIAL TO  
PREVENT INVERT CONCRETE  
FROM ENTERING SPACE BETWEEN  
PIPE AND FLEXIBLE BOOT

VILLAGE OF NEW LENOX  
STANDARD DETAIL  
FOR  
SANITARY MANHOLE PIPE  
CONNECTION

REV:	
DATE:	AUGUST 2014
FILE:	SANITARYSMNHLPC